

Darby Equipment PipeVac® Lifting System

Features

Safety First

We have put the solution right in the palm of the operator's hand with our new SmartLiftTechnology® wireless remote. Our transmitter lets the operator know if they have a safe lift or not - no guesswork required.

Hydraulic Drive

PipeVac Lifting Systems® are powered by the host machine's existing hydraulics. No longer is that noisy and expensive diesel or gas engine needed. Allowing you to save on fuel cost.

Smart Vacuum Pads

Our revolutionary new design allows you to safely lift a wider range of pipe diameters with fewer vacuum pads required. 40% more seal wear with PipeVac®.

Engineering

PipeVac Lifting Systems® meet ASME/ANSI B30.20 2013 and BTH, as well as being CE certified and OSHA compliant. You only need one PipeVac® model to meet your needs.

SmartLift Technology®

Every PipeVac Lifting System® manufactured with SmartLift Technology®. Each component is selected with safety, performance, and durability.



Specifications

Length	96" (2438.4 mm)
Width	30" (762 mm)
Height	37"/81" (939.8mm/2057.4 mm)
Weight	2,675 lbs (1,214 kgs)
Capacity	57,200 lbs (26 tonnes)

Operating parameters

Temperature	-40° F to 110° F (-40° C to 60° C)
Auxiliary Hydraulic Circuit	15,000 psi max

Custom applications are available.



SmartLift®
TECHNOLOGIES