


**10" Internal Pneumatic Clamp (IPC10)  
TECHNICAL SPECIFICATIONS AND FEATURES**



Pipe Size Range	10" (254mm)
Wall Thickness Range	.125"-.5" (3.18-12.7mm)
Standard Length	68" (1727.2mm)
Width	10" (254mm)
Height	10"(254mm)
Weight	235 lbs (107 kg)
Working Air Pressure	180-220 psi
Air Motor	Non Powered
Air Tank	2 gal
Clamping Shoes	15 total clamp shoes , 12 shoes at the joint (6 on each section) 3 shoes on rear section
Cylinder	6" (152mm)
Climbing Capability	N/A

**Features / Advantages**

- Filters, lubricators, regulators and valves all rated to 250psi
- Fully hardened dowel pins
- Nose cone made of 5/8" diameter CF round bar
- 3 Section Clamp - No frame - Nose cone only
- Three section, self-centering clamp has an extra clamping section to assure proper line-up in the pipe to avoid lost time for high-low adjustments. \*Standard in sizes 10" through 14"
- Darby uses grade 8 bolts and the highest quality seals and u-cups in our assemblies
- Air tubes are electro statically plated to reduce corrosion
- Spring mounted air tank
- Remote operated by reach rod